

Version: 4

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU



GLASS FIBRE

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: GLASS FIBRE

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Auxiliary product for the automotive. For professional user only. Uses advised against: All uses not specified in this section or in section 7.3

1.3 **Details of the supplier of the safety data sheet:**

Troton Sp. z o.o. Zabrowo 14A

78-120 Goscino - Zachodniopomorskie - Polska

Phone.: +48 94 35 123 94 -Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl

1.4 **Emergency telephone number:** (czynny od 8:00-16:00)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) no 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) no 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Lig. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372

2.2 **Label elements:**

CLP Regulation (EC) no 1272/2008:

Danger







Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313: IF exposed or concerned: Get medical advice/attention

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

2.3 Other hazards:

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable



GLASS FIBRE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixture:

Chemical description: Polyester resin

Components:

In accordance with Annex II of Regulation (EC) no1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS: EC:	100-42-5 202-851-5	Styrene Monomer	ATP ATP06	
Index:	601-026-00-0 1:01-2119457861-32- XXXX		Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	10 - <25 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

MASTER

Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

 $\ensuremath{\text{D.-}}$ Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 15 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:



According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Styrene Monomer	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	406 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	289 mg/m³	306 mg/m ³	85 mg/m ³	Non-applicable

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Styrene Monomer	Oral	Non-applicable	Non-applicable	2,1 mg/kg	Non-applicable
CAS: 100-42-5	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
EC: 202-851-5	Inhalation	174,25 mg/m ³	182,75 mg/m ³	10,2 mg/m ³	Non-applicable

PNEC:

Identification				
Styrene Monomer	STP	5 mg/L	Fresh water	0,028 mg/L
CAS: 100-42-5	Soil	0,2 mg/kg	Marine water	0,0028 mg/L
EC: 202-851-5	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0614 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the CE marking in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face mask	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection



According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 13,87 % weight
V.O.C. density at 20 °C: 30 kg/m³ (30 g/L)

Average carbon number: 8

Average molecular weight: 104,2 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Liquid

Viscous

Greenish

Not available

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 145 °C Vapour pressure at 20 °C: 622 Pa

Vapour pressure at 50 °C: 3297 Pa (3 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1800 kg/m³

Relative density at 20 °C: 1,82

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

>20,5 cSt

*Not relevant due to the nature of the product, not providing information property of its hazards.



GLASS FIBRE

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Non-applicable * Explosive properties: Non-applicable * Oxidising properties:

Flammability:

Flash Point: 32 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 490 °C
Lower flammability limit: Not available
Upper flammability limit: Not available

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

MASTER

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A.- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging the unborn child.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acut	Genus	
Styrene Monomer	LD50 oral	>2000 mg/kg	
CAS: 100-42-5	LD50 dermal	>2000 mg/kg	
EC: 202-851-5	LC50 inhalation	12 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Styrene Monomer	LC50	64.7 mg/L (96 h)	Carassius auratus	Fish
CAS: 100-42-5	EC50	0 4.7 mg/L (48 h) Daphnia magna		Crustacean
EC: 202-851-5	EC50	67 mg/L (192 h)	Microcystis aeruginosa	Algae

12.2 Persistence and degradability:



According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Styrene Monomer	BOD5	1.96 g O2/g	Concentration	100 mg/L
CAS: 100-42-5	COD	2.8 g O2/g	Period	14 days
EC: 202-851-5	BOD5/COD	0.7	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Identification Bioaccumulation p		nulation potential
Styrene Monomer	BCF	14
CAS: 100-42-5	Pow Log	2.95
EC: 202-851-5	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Styrene Monomer	Koc	Non-applicable	Henry	Non-applicable
CAS: 100-42-5	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 202-851-5	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) $n^{o}1907/2006$ (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:



According to 1907/2006/EC (REACH), 2015/830/EU

GLASS FIBRE

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: III

14.5 Dangerous for the environment:

14.6 Special precautions for user

Special regulations: 236, 340
Tunnel restriction code: E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

14.1 UN number: UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT

14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: III

14.5 Dangerous for the environment:

14.6 Special precautions for user

Special regulations: 236
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



14.1 UN number: UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT

14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: III
14.5 Dangerous for the environment: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the

IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable



GLASS FIBRE

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H226: Flammable liquid and vapour

H315: Causes skin irritation

H319: Causes serious eve irritation

H372: Causes damage to organs through prolonged or repeated exposure

H361d: Suspected of damaging the unborn child.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) no 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour

Repr. 2: H361 - Suspected of damaging fertility or the unborn child

Skin Irrit, 2: H315 - Causes skin irritation

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://esis.jrc.ec.europa.eu

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon



GLASS FIBRE

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.